

Gator XUV855D

Engine and Electrical

4-cycle diesel
3, OHV
23 hp (17.0 kW)
854cc
36.9 ft-lbs. (50 Nm) @2400 rpm
Liquid
480CCA
55 amp @ 3200 rpm, regulated, 540 watts

Lights

Two 37.5 watt halogen

On-demand True 4WD System

Auto-locking
Positive locking, mechanically actuated

Continuously Variable Transmission (CVT)
with full clutch enclosure
0-32 (0-52) Hi Forward, 0-15 (0-24) Lo Forward,
0-18 (0-29) Reverse

Two speed (hi-lo), oil bath
Hydraulic disc with twin piston front calipers
Driveline, internal wet multi-disc
Sealed, double-row ball

Suspension and Steering

Fully independent dual control arm with
adjustable spring preload
8 in. (203 mm)
Fully independent dual control arm with
adjustable spring preload and sway bar
9 in. (228.6 mm)
12.4 ft. (3.8 m)

Hitches

Standard 2 in. (50.8 mm) receiver

Occupant Protective System (OPS)

1.75 in. (44.4 mm) steel tube
3-point seat belts
SAE J2194 and OSHA ROPS

Ground Clearance

Front - 11.0 in. (280 mm), Rear - 11.0 in. (280 mm)
12.25 in. (311 mm)

Dimensions

119 in. (3035 mm)
62 in. (1571 mm)
51.4 in. (1305mm) / 51.4 in. (1305mm)
75 in. (1903 mm)
79 in. (2007 mm)
1,640 lb. (744 kg)
1,500 lb. (680 kg)
1,400 lb. (635 kg)

Cargo Box

Hybrid steel/glass-filled poly
45 x12 x52 (1143 x304.8x1320)
16.4 ft³ (0.46 m³)
1,000 lb. (454 kg)
Manual with lift assist shock (factory installed
power lift option)
Center truck-style latch

Tires, Front / Rear

27x9xR14 / 27x11xR14
26x9xR12 / 26x11xR12
25x9xR12 / 25x11xR12
Green & Yellow, Camouflage, Olive & Black

Gator XUV855D S4

4-cycle diesel
3, OHV
23 hp (17.0 kW)
854cc
36.9 ft-lbs. (50 Nm) @2400 rpm
Liquid
480CCA
55 amp @ 3200 rpm, regulated, 540 watts

Two 37.5 watt halogen

Auto-locking
Positive locking, mechanically actuated

Continuously Variable Transmission (CVT)
with full clutch enclosure
0-32 (0-52) Hi Forward, 0-15 (0-24) Lo Forward,
0-18 (0-29) Reverse

Two speed (hi-lo), oil bath
Hydraulic disc with twin piston front calipers
Driveline, internal wet multi-disc
Sealed, double-row ball

Fully independent dual control arm with
adjustable spring preload
8 in. (203 mm)
Fully independent dual control arm with
adjustable spring preload and sway bar
9 in. (228.6 mm)
17 ft. (5.2 m)

Standard 2 in. (50.8 mm) receiver

1.75 in. (44.4 mm) steel tube
3-point seat belts
SAE J2194 and OSHA ROPS

Front - 11.0 in. (280 mm), Rear - 11.0 in. (280 mm)
12.25 in. (311 mm)

154 in. (3912 mm)
62 in. (1571 mm)
51.4 in. (1305mm) / 51.4 in. (1305mm)
75 in. (1903 mm)
114 in. (2895.6 mm)
2018 lb. (915 kg)
1,500 lb. (680 kg)
1,400 lb. (635 kg)

Hybrid steel/glass-filled poly
45 x12 x52 (1143 x304.8x1320)
16.4 ft³ (0.46 m³)
1,000 lb. (454 kg)
Manual with lift assist shock (factory installed
power lift option)
Center truck-style latch

27x9xR14 / 27x11xR14
26x9xR12 / 26x11xR12
25x9xR12 / 25x11xR12

Green & Yellow, Camouflage

XUV855D / XUV855D S4

Diesel power to spare.

