FLOOR SCARIFIER TECHNICAL FEATURES





Part No	Engine	Drum Speed	FLC	Weight	Length	Width	Height	Noise
500.2004	Honda GX160 with cyclonic aircleaner	1800 rpm		49 kg	1130 mm	370 mm	900 mm	94 dBA
500.2000	Honda GX160	1800 rpm		49 kg	1130 mm	370 mm	900 mm	94 dBA
500.2004.240	Honda GX240 with cyclonic air cleaner	1800 rpm		58 kg	1130 mm	370 mm	900 mm	94 dBA
500.2000.240	Honda GX240	1800 rpm		58 kg	1130 mm	370 mm	900 mm	94 dBA
500.2001	Robin EY20 DUOA	1800 rpm		49 kg	1130 mm	370 mm	900 mm	94 dB(A)
500.2007	Robin EX17	1800 rpm		50 kg	1130 mm	370 mm	990 mm	94 dB(A)
500.2005	Kohler PA15102T Remote Air Cleaner	1800 rpm		53.5 kg	1130 mm	370 mm	900 mm	94 dB(A)
500.2006	Kohler PA911503 Cyclonic Air Cleaner	1800 rpm		49.0 kg	1130 mm	370 mm	900 mm	94 dB(A)
500-2100	Gast 8AM-FRV-2B	1800 rpm		49 kg	1130 mm	370 mm	900 mm	110 dBA)
500.2200.110	AEG 3HP 110/1/50	1800 rpm	28.0 amp	49 kg	1130 mm	370 mm	900 mm	90 dB(A)
500.2200.115	AEG 3HP 115/1/60	1800 rpm	28.0 amp	49 kg	1130 mm	370 mm	900 mm	90 dB(A)
500.2201.240	Lafert 3 HP 240/1/50	1800 rpm	12.5 amp	49 kg	1130 mm	370 mm	900 mm	90 dB(A)
500.2201.230	Lafert 3 HP 230/1/60	1800 rpm	12.5 amp	49 kg	1130 mm	370 mm	900 mm	90 dB(A)
500.2202.240	AEG 3 HP 220/240/3/50	1800 rpm	13.1 amp	49 kg	1130 mm	370 mm	900 mm	90 dB(A)
500.2202.415	AEG 3 HP 380/415/3/50	1800 rpm	4.8 amp	49 kg	1130 mm	370 mm	900 mm	90 dB(A)






This machine is fitted with the Honda GX160 Petrol Engine with Oil Alert as standard. It is also available with a cyclonic air cleaner. A heavier machine fitted with the GX240 is also available.



This machine is fitted with a Robin EY20 Petrol Engine with Oil Alert as standard. It is also available with a cyclonic air cleaner.



This machine is fitted with a 3 HP Electric Motor with Moeller switch gear with overload protection.



This machine is fitted with the Kohler PA15102T. Petrol Engine with Oil Alert as standard.

REMOTE AIR CLEANER

Fitted with a HANCOX remote air filtration system for longer engine life. This engine was based on the successful **KOHLER** Command 6 hp Engine





This machine is fitted with the Gast 8AM-FRV-2B Pneumatic Motor with Norgren Oil Fog Lubricator and Controls.



This machine is fitted with the AEG Electric Motor with Moeller Switch Gear, This configuration gives a soft start preventing the normal huge voltage surge caused when the unit is started. The control box has an easily accessible panic stop button and two metre trailing cable with 32 amp plug.

<u>6CM</u>