




Using the Rotary Hammer

- 1. Wear your protective equipment including ear defenders and goggles.
2. Never attempt to enlarge a hole that you have already drilled - the bit will jam.
3. Check on the biggest drill that your machine can use - if you overload it, the bit may jam, causing the drill to start to rotate. This can cause serious hand or wrist injury.
4. Watch out for signs that vibration may be affecting your hands. If your fingers start to tingle or feel numb, take a short break from using the machine. Exercise your fingers to encourage blood circulation. Ask the hire company for a copy of the HAE leaflet no. 2150 - Hand-arm vibration or visit www.hse.gov.uk/vibration
5. To help prevent vibration affecting your hands, operate the machine for shorter periods. Keep your hands warm - wearing gloves may help do this.
6. Keep the cable clear of the tool bit and any sharp edges on your work.
7. If you think the cable may be cut or damaged in any way, switch off and unplug at the mains before inspecting it. If the cable attached to the rotary hammer is damaged, stop using the machine. Contact the hire company. If an extension cable has been damaged, do not use it again.
8. Take care not to accidentally pull the plug from the socket.
9. Switch off and remove the plug from the socket before leaving the rotary hammer unattended.
10. If your equipment does not work properly do not attempt to repair it. Contact the hire company.
11. You may want to read this leaflet again. Please keep it until you finish work.

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

It is important to read all of this leaflet BEFORE you use the Rotary Hammer

- 1. Electricity is dangerous and must always be used with great care.
2. This rotary hammer is designed for drilling in concrete, masonry or brickwork.
3. The action of this rotary hammer can cause injury or damage if the machine is not used in a careful and controlled way.
4. If you have not used a rotary hammer before, familiarise yourself with the machine on some straightforward work before you start on the main task.
5. Plan your work and think ahead to make sure you will always be working safely.
6. You must have at least the following items of personal protective equipment: goggles: EN166 or BS2092; dust mask - a minimum of EN149 FFP3(s) protection; Safety boots to EN345 or BS1870/4972; industrial quality gloves; residual-current device (RCD) if using a 230 volt (mains) supply.
7. A personal first-aid kit should be available.
8. A rotary hammer must not be used by minors, or by anyone under the influence of drugs or alcohol.
9. A rotary hammer is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.
10. Although rotary hammer are designed for one person operation you should always be careful you do not lift beyond your own capabilities.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Soliuhull B37 7YE

Telephone: 44 (0) 121 380 4600
44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

v:032017

Any unauthorised reproduction - manually or electronically - is STRICTLY prohibited

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Soliuhull B37 7YE

Summary:
110V: Wall socket > transformer > any necessary extension cable > rotary hammer.
230V: Wall socket < RCD < extension cable < rotary hammer.

110 VOLT MACHINES (YELLOW PLUG)
Read the instructions below for your machine.
110V machines will have a yellow industrial plug fitted. 230V machines will have either a normal square pin plug fitted, or a blue industrial plug.
Your machine will only operate on one voltage: it will be 110V or 230V.
ELECTRICAL SAFETY
1. Switch the rotary hammer off, and unplug it before changing the drill bit.
2. This machine uses special drill bits with a slot or taper fixing.
3. You must only use the correct drill bits specifically for this rotary hammer. You must not use any other drill bits.

230 VOLT MACHINES (SQUARE PIN OR BLUE PLUG)
1. Use a residual current device (RCD) plugged directly in to the 230volt socket. Plug your machine into the RCD. This will help to protect you against electric shock if the cable or machine gets damaged.
2. Use the "TEST" button to check that the RCD is working each time you use it. Reset the RCD according to the instructions supplied with it.
3. If you need to use an extension cable, follow any special instructions given by the hire company. If the hire company has not given any special instructions, you should only use a suitably rated heavy duty one, not longer than 50 metres (160 feet). Plug it directly into the RCD.
4. Lay it out carefully avoiding liquids, sharp edges, doorways or windows where it might be trapped, and places where vehicles might run over it. Unroll it fully or it will overheat and could catch fire.
5. Make sure that any extension cable connections are dry and safe.

Useful Reference Points • www.hae.org.uk/businessguard



ROTARY HAMMER
1. Check your machine, cables, plugs and drill bits. If anything is found damaged, do not use the rotary hammer - contact the hire company.
2. Check that the plug on your machine matches your supply. Do not try to force connections or improvise them.
3. Machines with a cylindrical yellow industrial plug fitted are designed to run off an 110V supply. The hire company will have provided a portable transformer if you need to power the machine from a normal mains 230V supply. If a portable transformer has been supplied, take care not to injure yourself when moving it about - it may be heavier than you think. Machines designed to run directly from 230V mains will have either a normal square pin plug fitted, or a blue industrial plug.
4. Always use the side handle provided. Adjust it to the best position.
5. Vibration from using this rotary hammer can be hazardous. Warm your hands up before you start work, and wear gloves to keep your hands warm while you are working. Ask the hire company for a copy of the HAE leaflet no. 2150 -

WORK AREA
1. Do not use a rotary hammer where there is a danger of explosion. It will ignite fumes from petrol, or gas cylinders.
2. Make sure that the area is clear and safe and that no-one is near to you or could distract you.
3. Protect other people from the dust. Set up an exclusion zone around the area where the rotary hammer is being used with physical barriers, barrier tape and signs. Keep children and animals away when using this equipment.
4. Work should stop immediately should anyone, other than those directly assisting with the work, enter the exclusion zone.
5. Clear the area of trip hazards such as rubble, rubbish etc.
6. Do not use a rotary hammer in the rain or where it might get wet.
7. Drilling certain materials makes a large amount of dust - cover any surfaces or objects that may be damaged, or difficult to clean.
8. The following items of personal protective equipment (PPE) are the minimum that should be worn whenever you use this machine. Particular jobs or environments may require a higher level of protection.
9. You will need to wear an appropriate dust mask (with a minimum of EN149:2001 FFP3 protection) when you are in contact with material that causes dust.
10. You must wear safety boots (EN345 or BS1870/4972).

Operators