



4WD

Model		Foreman S/ES TRX500FM, TRX500FE	Foreman ES PS TRX500FPE
Classification		Heavy duty ATV	
Engine Type		475cc liquid-cooled, wet-sump, longitudinally mounted OHV 4-stroke single cylinder	
Bore x Stroke		92.0mm x 71.5mm	
Fuel System		38mm throttle-body fuel injection system	
Ignition		CDI	
Starter		Electric with auxiliary recoil	
Transmission		Five forward gears with reverse, auto clutch with manual (S) or electric shift (ES or ES PS)	
Drive		4wd Direct drive-shafts with TraxLok® switchable 2wd/4wd and full front wheel differential lock	
Power Steering		–	Power steering
Front Suspension		Independent double-wishbone with adjustable pre-load 185mm (7.28") travel	
Rear Suspension		Swingarm with single shock with adjustable pre-load 185mm (7.28") travel	
Front Brakes		190mm dual hydraulic discs	
Rear Brake		160mm sealed mechanical drum	
Front Tyres		25 x 8-12	
Rear Tyres		25 x 10-12	
Dimensions	L	2103mm	
	W	1205mm	
	H	1219mm	
Wheelbase		1286mm	
Seat Height		869mm	
Ground Clearance		190mm	
Min. Turning Radius		3200mm	
Fuel Capacity		14.7L, incl. 4.9L reserve	
Dry weight		S: 275kg ES: 275kg	ESPS: 282kg
Colours		Red and Green (TRX500 FM only). Optional green panel kits available	