

Concrete & Asphalt > C99 Floor Saw

The Clipper **C99** is a compact and economical floor saw, for wet or dry cutting of asphalt or concrete. The outstanding cutting performance is obtained by the optimal weight distribution. The positioning of the 20 litre water tank adds weight onto the blade while maintaining an excellent view of the cutting operation. By means of a handwheel the operator can adjust the

cutting depth, indicated by a gauge (patent pending). The handle is adjustable to the operator height and stays level at any cutting depth. Vibration is kept to a minimum with the heavy-duty frame of the C99 which will extend the machine life and add confort to the operator. The best performance is obtained with genuine Norton dry or wet cutting diamond blade.

Norton reserves the right to incorporate design and modifications without prior notice. FT214-UK07/00 imedia

Concrete & Asphalt ▶ C99 Floor Saw

Features

- ▶ Continuous depth control with a handwheel. The depth is indicated by a gauge (patent pending).
- ► Easy to service 4 V belts drive.
 - ▶ Cutting depth up to 140 mm.
 - ▶ Removable 20 litre polyurethane water tank with large opening for filling, Inbuild coupling for external water supply.
 - ▶ Easely adjustable handle to the size of the operator. The handle stays at the same level at any cutting depth.
 - ▶ Vibration reduced by heavy duty frame.
 - ▶ Optimal weight distribution results in outstanding cutting performance.
 - ▶ Shaft locking device for easy blade removing. Pivoting blade guard, stays permanently on the machine.
 - ▶ Standard 20 mm twin blade mounting.
 - Lifting hook in the center of gravity of the floor saw.
- Easy access to the fuel tank.
- All neccessary tools stored on the control panel.
- Rear wheels and blade shaft bearings equipped with grease nipples.
- ▶ Rear wheel in recess from the cut and permits to cut in parallel of an open trench.
- Parking brake for safety.
- ► Heavy duty pillow block bearings on 30mm blade shaft.



Ergonomic working condition



Easy blade mounting. Parking brake

Specifications

Model

Model C99 PI3H	
Petrol Honda GX390	9,6 kW (13HP)
Model C99 P13H CYCLONIC	
Petrol Honda GX390	9,6 kW (13HP)
Model C99 PI3K	
Petrol Kohler CH13T	9,6 kW (13HP)
Modell C99 D7	
Diesel HATZ 1B30	5 kW (7HP)
Modell C99 E75.3	
Electric	5,5 kW 400 V 3~

Characteristics

Max. blade	Ø	400 mm
Max. depth of cut	ø400	140 mm
	ø350	115 mm
Bore		25,4 mm
Twin blade mounting		20 mm
Blade shaft speed		2850 min ⁻¹
V-Belts		4
Water capacity		20 L
Sound pressure (Honda)		88 dB(A)
Sound power (Honda)		105 dB(A)

Dimensions / Weight

Length (V	Vorking)	1160 mm
Length (Tr	ransport)	850 mm
Width		512 mm
Height		990 mm
Weight	Honda	99 kg
	Kohler	III kg
	Hatz	107 kg
	Elektro	105 kg



Deph gauge, lifting hook.



Designed for use with Clipper wet or dry cutting diamond blades

www.norton-diamond.com

NORTON DIAMOND PRODUCTS

Unit 2, Meridian West Meridian Business Park Leicester LE3 2WX, England www.norton-diamond.com nlesal@norton.saint-gobain.com Tel.: +44 (0116) 263 23 02 Fax: +44 (0116) 282 72 92 Free Fax: 0800 62 23 85 Sold and supported by: